


ROAD SAFETY

BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



SUREFOOT TRENCH COVERS

SUREFOOT 1600 (1665 x 1285MM)

SUREFOOT 1220 (1285 x 862MM)

SUREFOOT 1080 (1147 x 1147 MM)

EDGED DRIVEWAY BOARD

STOCK CODE: SUREFOOT 1600: 104320, SUREFOOT 1220: 104319, SUREFOOT 1080: 102820



TRICEL
GENERATIONS OF INNOVATION

STOCK CODE:
SUREFOOT 1600: 104320
SUREFOOT 1220: 104319
SUREFOOT 1080: 102820

SUREFOOT TRENCH COVERS



SUREFOOT 1600 (1665 x 1285MM), SUREFOOT 1220 (1285 x 862MM), SUREFOOT 1080 (1147 x 1147 MM)

EDGED DRIVEWAY BOARD

Designed for covering holes and trenches during maintenance, construction and repair projects.

Provide safe passageways for pedestrians and vehicles up to 3.5 tonnes (see load ratings on page 4).

Top view and profile view of SUREFOOT 1600



ROAD SAFETY

BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



* Approximate dimensions.

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.

Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk



STOCK CODE:
SUREFOOT 1600 : 104320
SUREFOOT 1220 : 104319
SUREFOOT 1080: 102820

SUREFOOT TRENCH COVERS


SUREFOOT 1600 (1665 x 1285MM), SUREFOOT 1220 (1285 x 862MM), SUREFOOT 1080 (1147 X 1147 MM)

EDGED DRIVEWAY BOARD

Top view and profile view of SUREFOOT 1220



**ROAD
SAFETY**
BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



* Approximate dimensions.
In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.
Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk




STOCK CODE:
SUREFOOT 1600 : 104320
SUREFOOT 1220 : 104319
SUREFOOT 1080: 102820

SUREFOOT TRENCH COVERS

SUREFOOT 1600 (1665 x 1285MM), SUREFOOT 1220 (1285 x 862MM), SUREFOOT 1080 (1147 X 1147 MM)

EDGED DRIVEWAY BOARD

Top view and profile view of SUREFOOT 1080



**ROAD
SAFETY**
BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



* Approximate dimensions.
In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.
Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk

STOCK CODE:
SUREFOOT 1600: 104320
SUREFOOT 1220: 104319
SUREFOOT 1080: 102820

SUREFOOT TRENCH COVERS

SUREFOOT 1600 (1665 x 1285MM), SUREFOOT 1220 (1285 x 862MM), SUREFOOT 1080 (1147 x 1147 MM)

EDGED DRIVEWAY BOARD



ROAD SAFETY

BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



RSPA
Member

DIMENSIONS

Available in three sizes:

- SUREFOOT 1600 (1665 x 1285mm) weight = 32.3kgs
- SUREFOOT 1220 (1285 x 862mm) weight = 17.4kgs
- SUREFOOT 1080 (1147 x 1147mm) weight = 22kgs

KEY FEATURES

- Comply with HAUC's 2018/01 advice note.
- Fully compliant with current UK & European Legislation.
- Tough, lightweight & durable (constructed from SMC).
- Improved stability & reduced movement (PVC edge).*
- Four pre-moulded fixing holes available for certain applications.
- Reduced trip hazard with a 6mm non-trip leading edge. The lowest leading edge profile currently on the market.
- Highest rated anti-slip in UK & exceeds HSE slip resistance (BS 7976: Part 2 / BS EN 13036-4).
- Electric shock safe.

*Additional securing may be required for certain applications.

SPECIFICATIONS

- Max load of 3.5 tonnes (see load ratings below)
 - High strength to weight ratio
- SUREFOOT 1600 (1665 x 1285mm)
SUREFOOT 1220 (1285 x 862mm)
SUREFOOT 1080 (1147 x 1147mm)

Load Rating:

- Surefoot 1600: 3.5 tonne vehicle loading over a 900mm trench
- Surefoot 1220: 3.5 tonne vehicle loading over a 700mm trench
- Surefoot 1080: 3.5 tonne vehicle loading over a 500mm trench

* Approximate dimensions.
In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.
Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk

STOCK CODE:
SUREFOOT 1600: 104320
SUREFOOT 1220: 104319
SUREFOOT 1080: 102820


SUREFOOT TRENCH COVERS

SUREFOOT 1600 (1665 x 1285MM), SUREFOOT 1220 (1285 x 862MM), SUREFOOT 1080 (1147 X 1147 MM)

EDGED DRIVEWAY BOARD

ROAD SAFETY

BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



SAFETY

- Approved by local authorities and major utility companies.
- Department for Transport compliant (Safety at Street Works and Road Works and Practical guide for Street Works).
- DETR compliant (Best Practice in Street Works and Highway Works).
- Complies to and exceeds the directives and specifications in the latest Street Works regulations and Directive 2017 relating to Ramps, Trench Covers and Road Plates.
- Complies to and exceeds T/SP/E42 National Grid specification for Ramps, Trench Covers and Road Plates.

STORAGE & HANDLING

- Storage: Store Flat
Handling: 2 man lift, do not walk on leading edge



TRICEL
GENERATIONS OF INNOVATION

* Approximate dimensions.

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.


Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.

Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk


104319-104320-102820-1198031/3-MAR2023

ROAD SAFETY

BY TRICEL



UK'S LEADING
DESIGNER & MANUFACTURER



INSTALLATION GUIDE SUREFOOT TRENCH COVERS



TRICEL
GENERATIONS OF INNOVATION

104319-104320-102820-1198031/3-MAR2023

MAINTENANCE & INSPECTION

CHECK FOR SIGNS OF DAMAGE



Ensure that the product is lying flat on the ground. If there are cracks in the yellow section or a visible bend on the board this indicates improper use has caused damage.

Any boards displaying this kind of damage should be disposed of.



Inspect each product for signs of damage, between every installation.



To maintain anti-slip properties, make sure to clean product between every installation and remove any visible debris.



When fitting the product in place, never drop the product, gently lower it in place. Never lift or move with machinery. Never walk the product leading edge.



TRICEL
GENERATIONS OF INNOVATION

* Approximate dimensions.

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.

Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk

104319-104320-102820-1198031/3-MAR2023









INSTALLATION & MANUAL HANDLING GUIDELINES



Always carry out a risk assessment to ensure that the usage of a Trench Cover is a suitable solution for your scenario.

UNEDGED

EDGED

PRODUCT	DIMENSIONS	LOAD RATING	 MAX TRENCH WIDTH FOR VEHICLE CROSSING	 MAX TRENCH WIDTH FOR PEDESTRIAN CROSSING	HOW MANY PEOPLE TO LIFT?
TRENCH COVER	1080x1080	3.5 TONNE VEHICLE	OVER 500MM	OVER 700MM	
TRENCH COVER	1220x800	3.5 TONNE VEHICLE	OVER 700MM	OVER 900MM	
TRENCH COVER	1600x1220	3.5 TONNE VEHICLE	OVER 900MM	OVER 1100MM	
SUREFOOT 1080	1080x1080	3.5 TONNE VEHICLE	OVER 500MM	OVER 700MM	
SUREFOOT 1220	1285x862	3.5 TONNE VEHICLE	OVER 700MM	OVER 900MM	
SUREFOOT 1600	1665x1285	3.5 TONNE VEHICLE	OVER 900MM	OVER 1100MM	

Overlap – 150mm / 6" for all boards



TRICEL
GENERATIONS OF INNOVATION

* Approximate dimensions.
In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.
Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk

104319-104320-102820-1198031/3-MAR2023

INSTALLATION & SAFE HANDLING




Follow the process below for safe and effective installations.

Risk assessments should be carried out to ensure the usage is suitable for the scenario.




Two person lift.


Ensure to bend at the knees when lowering the trench cover in place.



Always position the trench cover board centrally over the trench as illustrated.



Ensure a minimum overlap of 150mm for every board.



Repeat until the whole trench is covered.



TRICEL
GENERATIONS OF INNOVATION

* Approximate dimensions.

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.

Tel: +44 1453 791616 | Email: constructionsales@tricel.co.uk | www.tricel.co.uk

104319-104320-102820-1198031/3-MAR2023