

PLASTIC SAFE GRAFFITI REMOVER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 22/02/2021 Version: 10.5

Generated: 02/03/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : PLASTIC SAFE GRAFFITI REMOVER

UFI : F5U3-90A8-R00R-UFGY

Product code K175 Type of product : Aerosol Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

Use of the substance/mixture : plastic safe graffiti remover for solvent sensitive surfaces

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SELDEN RESEARCH LIMITED SELDEN EUROPE B.V.

STADEN LANE BUXTON DERBYSHIRE SK17 9R7 UNITED KINGDOM

Tel: +31 (0) 43 363 42 89 Tel: 01298 26226 Fax: 01298 26540 Email: sds@selden.eu

WATERMOLEN 13

6229 PM MAASTRICHT

NEDERLAND

Email: safety@selden.co.uk

1.4. Emergency telephone number

Mon to Fri 8.30am to 5.00pm - 01298 26226 Tel: +31 (0) 43 363 42 89

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

H222:H229 Aerosol, Category 1 Skin corrosion/irritation, Category 2 H315 H319 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

Signal word (CLP) Danger

Contains 1-methoxy-2-propanol; monopropylene glycol methyl ether

Document generated @ 02/03/2022 16:57:22 Page 1 of 10

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation. H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of soap, water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

°F.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3-butoxypropan-2-ol; propylene glycol monobutyl ether	(CAS-No.) 5131-66-8 (EC-No.) 225-878-4 (EC Index-No.) 603-052-00-8 (REACH-no) 01-2119475527-28	15 – 30	Eye Irrit. 2, H319 Skin Irrit. 2, H315
1-methoxy-2-propanol; monopropylene glycol methyl ether	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3 (REACH-no) 01-2119457435-35	15 – 30	Flam. Liq. 3, H226 STOT SE 3, H336
butane substance with national workplace exposure limit(s) (IE, GB)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	5 – 10	Flam. Gas 1A, H220 Press. Gas
Alcohol Alkoxylate	(CAS-No.) 166736-08-9 (REACH-no) Exempt/Polymer	5 – 10	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
propane substance with national workplace exposure limit(s) (IE)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	5 – 10	Flam. Gas 1A, H220

Document generated @ 02/03/2022 16:57:22 Page 2 of 10

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
		(1 <c 10)="" 2,="" eye="" h319<br="" irrit.="" ≤="">(10 <c 1,="" 100)="" <="" dam.="" eye="" h318<="" td=""></c></c>

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation : High concentration of vapours may induce: headache, nausea, dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Explosion hazard : Explosion risk in case of fire.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

6.2. Environmental precautions

Avoid release to the environment.

Document generated @ 02/03/2022 16:57:22 Page 3 of 10

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not pierce or burn, even after use.

Precautions for safe handling : Do not spray on an open flame or other ignition source. Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/122 °F.

Incompatible products : Oxidizing agent. Strong acids. Strong bases. Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (106-97-8)		
Ireland - Occupational Exposure Limits		
Local name	Butane	
OEL TWA [2]	1000 ppm	
United Kingdom - Occupational Exposure Limits		
Local name	Butane	
WEL TWA (OEL TWA) [1]	1450 mg/m³	
WEL TWA (OEL TWA) [2]	600 ppm	
WEL STEL (OEL STEL)	1810 mg/m³	
WEL STEL (OEL STEL) [ppm]	750 ppm	
Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	

propane (74-98-6)	
Ireland - Occupational Exposure Limits	
Local name	Propane
OEL TWA [2]	1000 ppm
Notes (IE)	Asphx

8.1.2. Recommended monitoring procedures

No additional information available

Document generated @ 02/03/2022 16:57:22 Page 4 of 10

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. EN 166

8.2.2.2. Skin protection

Skin and body protection:

If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Hand protection:

Chemical resistant gloves (according to European standard EN 374 or equivalent). Nitrile rubber gloves

Other skin protection

Materials for protective clothing:

Not required for normal conditions of use

8.2.2.3. Respiratory protection

Respiratory protection:

Not required for normal conditions of use

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosol.
Colour : Colourless.
Odour : characteristic.

Document generated @ 02/03/2022 16:57:22

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold : No data available

pH : 7

Relative evaporation rate (butylacetate=1) : No data available Melting point No data available Freezing point No data available Boiling point No data available Flash point No data available Auto-ignition temperature : No data available : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapour pressure Relative vapour density at 20 °C : No data available

Relative density : 0.83

Solubility : immiscible and insoluble.

Partition coefficient n-octanol/water (Log Pow) : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidising properties : No data available Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

10.5. Incompatible materials

None under normal use.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

pH: 7

Serious eye damage/irritation : Causes serious eye irritation.

pH: 7

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified

Document generated @ 02/03/2022 16:57:22

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

1-methoxy-2-propanol; monopropylene glycol methyl ether

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

GRAFFITI REMOVER

Vaporizer Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

: Not classified

Alcohol Alkoxylate (166736-08-9)	
LC50 - Fish [1]	10 – 100 mg/l
EC50 - Crustacea [1]	10 – 100 mg/l
ErC50 other aquatic plants	10 – 100 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not pierce or burn, even after use.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

Document generated @ 02/03/2022 16:57:22 Page 7 of 10

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.1 UN number

UN-No. (ADR) : UN 1950 UN-No. (IMDG) : UN 1950 UN-No. (IATA) : UN 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS

Proper Shipping Name (IATA) : Aerosols, flammable

Transport document description (ADR)

: UN 1950 AEROSOLS, 2.1, (D)

Transport document description (IMDG)

: UN 1950 AEROSOLS, 2.1

Transport document description (IATA)

: UN 1950 Aerosols, flammable, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I

Document generated @ 02/03/2022 16:57:22 Page 8 of 10

PLASTIC SAFE GRAFFITI REMOVER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Air transport

Stowage category (IMDG)

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

United Kingdom

British National Regulations : Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No

1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH).

Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.

15.2. Chemical safety assessment

No additional information available

Document generated @ 02/03/2022 16:57:22 Page 9 of 10

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 3	Flammable liquids, Category 3	
Press. Gas	Gases under pressure	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Document generated @ 02/03/2022 16:57:22 Page 10 of 10