Benchmark

BMG456



NITRILE, POWDER-FREE, SINGLE USE GLOVE

Lightweight, powder-free, single-use gloves with textured fingertips.

FEATURES

- > 100% premium quality nitrile, thickness 0.1mm
- > Textured finish on the fingertips to enhance grip
- > Lightweight and comfortable with a 'second skin' feel
- > Powder-free, non-sterile
- > Conforms to EN455 (parts -1, -3 &-4)
- Category III
- > AQL 4.0
- > Latex free
- > Beaded cuff
- Thickness 0.10mm (5g)



SUITABLE FOR


Typical Industries

- Aerospace
- Chemical
- Electronics
- Food
- Pharmaceutical
- Manufacturing
- Oil and Gas

Suitable Applications

- Chemical Handling
- Food Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION



See overleaf for explanation



RECOMMENDATIONS FOR USE USE: Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement STORAGE : Store in dry conditions in the original packaging and

 CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no

LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure

away from direct sunlight

the glove is suitable for its intended use

damage is present.

Benchmark

BMG456



PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	-
COLOUR	Blue	
LENGTH (mm)	240 mm	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6½-7/S	BMG00456DD	100 singles per
7½-8/M	BMG00456DF	box
8½-9/L	BMG00456DH	10 boxes per
9½-10/XL	BMG00456DJ	case

CERTIFICATION LEGENDS

R

D

G

н

/	-/

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016 CODE CHEMICAL CHEMICAL

CODE Methanol Acetone Acetonitrile Dichloromethane Carbon Disulfide М Ν Toluene 0

Diethylamine Tetrahydrofurane Ethyl acetate S

EN455-1:	Freedom from holes
EN455-2:	Physical properties
EN455-3:	Biological evaluation
EN455-4:	Shelf Life

Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide 30% Hydrogen peroxide 40% Hydrofluoric acid

n-Heptane

37% Formaldehyde

PE OF OVES	BREAKTHROUGH TIME
A	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical

TYP GL (



 \mathfrak{B}

FOOD CONTACT

MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

PROTECTION AGAINST

DIRECTIVE 2002 / 72 EC

EUROPE

www.globus.co.uk

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +971 4 882 9962
- F: +971 4 882 9963

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2021 Globus (Shetland) Ltd | BMK-DATA-456 0121 2

EU Type-Examination Certificate issued by INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified body 2575)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary