



Kirk Sandall Industrial Estate, Doncaster, South  
Yorkshire, DN3 1QR

+44 (0)1302 310 113  
enquiries@prosolveproducts.com  
www. prosolveproducts.com

ProSolve is trademark of S.T.L Trading Company  
Limited  
Reg in England No: 5230722  
VAT Reg No: 381 3533 58

## TECHNICAL DATA SHEET

PRO SOLVE™ CARPET PROTECTOR FILM (CP100/610S, CP60/1210S, CP60/610/25MS,  
CP/610/50MS, CP60/610S, CPRW60/610/25MS, CPRW60/610/50MS AND CPRW60/610S)

### DESCRIPTION

ProSolve self-adhesive Carpet Protector is a clear, waterproof film that protects all carpets from the dirt, stains and spills that occur during painting, building, plastering and general maintenance work. When the job is complete, simply peel the film from the carpet and discard.

ProSolve carpet protector is also ideal for a multitude of uses in industrial and commercial applications.

### APPLICATION

Check compatibility with carpet in an inconspicuous area prior to application. Place roll on floor facing the direction it is to be applied and unpeel approx. 300mm (12") of film. Press onto the floor, then simply continue to unwind the roll whilst pressing down and smoothing the film as you go.

### LIMITATIONS

#### **Not suitable for wool carpets.**

Check that ProSolve carpet protector is firmly stuck to carpet before commencing work.

ProSolve carpet protector can leave a sticky residue on some surfaces, this can be easily removed by cleaning.

Remove within 4 weeks to prevent any sticky residue being left on carpet.

In areas of heavy footfall; or when temperatures are in excess of 22°C; remove ProSolve carpet protector after a maximum of one week.

In the event of any sticky residue remaining after removal; simply clean carpets with carpet cleaner or warm, soapy water.

Do not use underfloor heating whilst ProSolve carpet protector is in use (or 24 hours prior to application).

## WARNING

This product may become slippery when wet. Mop up any spills immediately or replace ProSolve carpet protector where necessary.

## SPECIFICATION

SKU	CP100/610S	CP60/1210S	CP60/610/25	CP/610/50	CP60/610S	CPRW60/610/50	CPRW60/610S
Colour	Transparent	Transparent	Transparent	Transparent	Transparent	Transparent	Transparent
Heat Resistant	65°C	65°C	65°C	65°C	65°C	65°C	65°C
Viscosity	650gf/25mm	650gf/25mm	650gf/25mm	650gf/25mm	650gf/25mm	650gf/25mm	650gf/25mm
Thickness(mm)	0.1	0.06	0.06	0.06	0.06	0.06	0.06
Breaking Elongation	Trasv> 300% Longi> 180%	Trasv> 300% Longi> 180%	Trasv> 300% Longi> 180%	Trasv> 300% Longi> 180%	Trasv> 300% Longi> 180%	Trasv> 300% Longi> 180%	Trasv> 300% Longi> 180%
Break Strength	Trasv> 8N/25mm Longi> 15N/25mm	Trasv> 8N/25mm Longi> 15N/25mm	Trasv> 8N/25mm Longi> 15N/25mm	Trasv> 8N/25mm Longi> 15N/25mm	Trasv> 8N/25mm Longi> 15N/25mm	Trasv> 8N/25mm Longi> 15N/25mm	Trasv> 8N/25mm Longi> 15N/25mm
Base Material	PE	PE	PE	PE	PE	PE	PE
Adhesive	Water-based acrylic	Water-based acrylic	Water-based acrylic	Water-based acrylic	Water-based acrylic	Water-based acrylic	Water-based acrylic

## IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.

